


# EMERGENCY TEST BUTTON

specifications for emergency test button, wall mounted with single gang

## DEDICATED TEST BUTTON

By default, the emergency test button runs a 30-second test when pressed. Test buttons can also be configured to run a 90-minute test. Test fixtures are grouped within zones in the software.



### PROJECT INFORMATION

<b>CATALOG #:</b>	
<b>TYPE:</b>	
<b>PROJECT:</b>	
<b>SPECIFIER:</b>	

### SPECIFICATIONS

<b>Connect Software Requirements</b>	Minimum V1.1
<b>Peripheral Communications Bus</b>	2-twisted pairs 18-24 AWG Stranded or Solid wire 1 Pair - 1 Mbps differential data pair - CAN 2.0 (ISO 11898-2) 1 Pair - +12 VDC @ 500mAmps Maximum
<b>Single Gang</b>	Fits in a standard single gang mud ring or wall box.

### ENVIRONMENTAL SPECIFICATIONS

<b>Safety Compliance</b>	Compliant with UL 924 & UL 2108
<b>ROHS</b>	Compliant
<b>Normal Operating Temperature and Altitude (Density Altitude)</b>	-5°C to +45°C (+23°F to +113°F), up to 5000ft (1500m) -5°C to +40°C (+23°F to +104°F), up to 10,000ft (3000m) Min ambient temperature for cold start is 0°C (+32°F)
<b>Relative Humidity</b>	10% to 95%, noncondensing
<b>Storage Environment</b>	Temperature: -20°C to +80°C (-4°F to +158°F) Altitude: 15,000 ft
<b>Location</b>	For use in dry locations.

**CABLING AND CONNECTOR CONSIDERATIONS**  
available at [PLATFORMATICS.com](https://www.platformatics.com)

## ordering information

PRODUCT	CONNECTOR
<b>POE-WT1-B-W-</b> Emergency Test Button, Wall Mount	<b>ST</b> Screw Terminal

Sample: **POE-WT1-B-W-ST**

