


EMERGENCY TEST BUTTON

specifications for emergency test button, wall mounted with single gang

DEDICATED TEST BUTTON

By default, the emergency test button runs a 30-second test when pressed. Test fixtures are grouped within zones in the software.



PROJECT INFORMATION

CATALOG #:	
TYPE:	
PROJECT:	
SPECIFIER:	

SPECIFICATIONS

PAC Software Requirements	Minimum V1.1
Peripheral Communications Bus	2-twisted pairs 18-24 AWG Stranded or Solid wire 1 Pair - 1 Mbps differential data pair - CAN 2.0 (ISO 11898-2) 1 Pair - +12 VDC @ 500mAmps Maximum
Single Gang	Fits in a standard single gang mud ring or wall box.

ENVIRONMENTAL SPECIFICATIONS

Safety Compliance	Compliant with UL 924 & UL 2108
ROHS	Compliant
Normal Operating Temperature and Altitude (Density Altitude)	-5°C to +45°C (+23°F to +113°F), up to 5000ft (1500m) -5°C to +40°C (+23°F to +104°F), up to 10,000ft (3000m) Min ambient temperature for cold start is 0°C (+32°F)
Relative Humidity	10% to 95%, noncondensing
Storage Environment	Temperature: -20°C to +80°C (-4°F to +158°F) Altitude: 15,000 ft
Location	For use in dry locations.

CABLING AND CONNECTOR CONSIDERATIONS
available at [PLATFORMATICS.COM](https://www.platformatics.com)

ordering information

PRODUCT	CONNECTOR
POE-WT1-B-W- Emergency Test Button, Wall Mount	ST Screw Terminal

Sample: **POE-WT1-B-W-ST**

